

General information

The system is used for optical transmission of audio- and video- signals. The transmitter consists an internal microphone, video-IN and a connector

Technical Data

Transmitter:

Microphone:	mono (internal) or external via 3,5 mm jack
Line IN:	standard level, stereo, via 3,5 mm jack
Bandwidth (-3dB):	60 Hz to 15 kHz
Video IN:	standard level, impedance 75 Ω , 3-poliger, geschirmter Sensorstecker mit Stromversorgung für Mini-Videokamera
Power supply:	internal 5 X NiMH cells: 6 V, 4 Ah
Operating time:	> 20 hours
Dimensions (LxWxH):	136 mm x 84 mm x 65 mm
Weight:	800 g

Receiver:

Audio OUT:	internal speaker, additional external speaker via 3,5mm jack
Line OUT:	standard level, impedance 2,2 k Ω
Video OUT:	Standard level, impedance 75 Ω
Power supply:	internal 5 X NiMH cells: 6 V, 4 Ah or power supply unit
Operating time:	> 20 hours
Dimensions (LxWxH):	220 mm x 160 mm x 60 mm
Weight:	900 g

Mini camera:

Dimensions (LxWxH):	60 mm x 40 mm x 40 mm
Technical features:	PAL, Video (colour)